



DATASHEET

TECO IE3 FLAMEPROOF (EXD) TEFC

MOTOR SERIES	TECO IE3 FLAMEPROOF (EXD) TEFC	
START METHOD		DIRECT ON LINE
KW RATING		0.75
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		8
FRAME		100L
SPEED		
SYNCHRONOUS	(rpm)	750
FULL LOAD	(rpm)	700
CURRENT		
FULL LOAD	(Amps)	2.27
LOCKED ROTOR	%	440
TORQUE		
FULL LOAD TORQUE	(Nm)	10.2
STARTING TORQUE	%	235
MINIMUM TORQUE	%	220
BREAKDOWN TORQUE	%	230
ROTOR INERTIA (J = GD ² /4)	(Kgm ²)	0.0105
EFFICIENCY		
100% LOAD	%	76.5
75% LOAD	%	76.5
50% LOAD	%	73
POWER FACTOR		
100% LOAD	%	60
75% LOAD	%	50.5
50% LOAD	%	38.5
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		56
WEIGHT OF MOTOR	kgs	52
BEARINGS		
DRIVE END		6206 ZZ C3
NON DRIVE END		6305 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	49
DESIGN STANDARD		BS4999, IEC60034, IEC60079-1:2014, IEC60079-0:2011
CERTIFICATION		Ex db, IIB, T4, Gb and Ex db, I, Mb both -20°C < Tamb < 55°C
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C