



# DATASHEET

## MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

<b>MOTOR SERIES</b>	MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
<b>START METHOD</b>			DIRECT ON LINE
<b>KW RATING</b>			0.75
<b>VOLTAGE</b>	(V)		240
<b>PHASES</b>			3
<b>FREQUENCY</b>	(Hz)		50
<b>NO OF POLES</b>			8
<b>FRAME</b>			100L
<b>SPEED</b>			
	SYNCHRONOUS	(rpm)	750
	FULL LOAD	(rpm)	700
<b>CURRENT</b>			
	FULL LOAD	(Amps)	3.93
	LOCKED ROTOR	%	441
<b>TORQUE</b>			
	FULL LOAD TORQUE	(Nm)	10.23
	STARTING TORQUE	%	258.5
	MINIMUM TORQUE	%	242
	BREAKDOWN TORQUE	%	253
<b>ROTOR INERTIA (J = GD<sup>2</sup>/4)</b>		(Kgm <sup>2</sup> )	0.0011
<b>EFFICIENCY</b>			
	100% LOAD	%	76.6
	75% LOAD	%	76.5
	50% LOAD	%	73
<b>POWER FACTOR</b>			
	100% LOAD	%	60
	75% LOAD	%	50.5
	50% LOAD	%	38.5
<b>INSULATION CLASS</b>			H
<b>ENCLOSURE TYPE</b>			TEFC
<b>IP RATING</b>			66
<b>WEIGHT OF MOTOR</b>		kgs	39
<b>BEARINGS</b>			
	DRIVE END		6206 ZZ C3
	NON DRIVE END		6305 ZZ C3
<b>NO LOAD SOUND PRESSURE LEVEL @ 1M</b>		dbA	49
<b>DESIGN STANDARD</b>			AS1359
<b>CERTIFICATION</b>			
<b>TEMPERATURE RISE ABOVE AMBIENT</b>			< 80 DEG C