



DATASHEET

TECO IE3 FLAMEPROOF (EXD) TEFC

MOTOR SERIES	TECO IE3 FLAMEPROOF (EXD) TEFC	
START METHOD		DIRECT ON LINE
KW RATING		1.5
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		6
FRAME		100L
SPEED		
SYNCHRONOUS	(rpm)	1000
FULL LOAD	(rpm)	950
CURRENT		
FULL LOAD	(Amps)	3.47
LOCKED ROTOR	%	720
TORQUE		
FULL LOAD TORQUE	(Nm)	15.1
STARTING TORQUE	%	235
MINIMUM TORQUE	%	225
BREAKDOWN TORQUE	%	280
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.0148
EFFICIENCY		
100% LOAD	%	82.5
75% LOAD	%	84
50% LOAD	%	81.5
POWER FACTOR		
100% LOAD	%	73
75% LOAD	%	67
50% LOAD	%	54
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		56
WEIGHT OF MOTOR	kgs	52
BEARINGS		
DRIVE END		6206 ZZ C3
NON DRIVE END		6305 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	47
DESIGN STANDARD		BS4999, IEC60034, IEC60079-1:2014, IEC60079-0:2011
CERTIFICATION		Ex db, IIB, T4, Gb and Ex db, I, Mb both -20°C < Tamb < 55°C
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C