



DATASHEET

TECO IE3 FLAMEPROOF (EXD) TEFC

MOTOR SERIES	TECO IE3 FLAMEPROOF (EXD) TEFC	
START METHOD		DIRECT ON LINE
KW RATING		15
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		160L-4P
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1465
CURRENT		
FULL LOAD	(Amps)	26.2
LOCKED ROTOR	%	774
TORQUE		
FULL LOAD TORQUE	(Nm)	97.6
STARTING TORQUE	%	245
MINIMUM TORQUE	%	195
BREAKDOWN TORQUE	%	285
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.1155
EFFICIENCY		
100% LOAD	%	92.5
75% LOAD	%	93
50% LOAD	%	92.5
POWER FACTOR		
100% LOAD	%	86
75% LOAD	%	83
50% LOAD	%	74.5
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		56
WEIGHT OF MOTOR	kgs	197
BEARINGS		
DRIVE END		6309 ZZ C3
NON DRIVE END		6307 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	57
DESIGN STANDARD		BS4999, IEC60034, IEC60079-1:2014, IEC60079-0:2011
CERTIFICATION		Ex db, IIB, T4, Gb and Ex db, I, Mb both -20°C < Tamb < 55°C
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C