



DATASHEET

MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

MOTOR SERIES	MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
START METHOD			DIRECT ON LINE
KW RATING			1.5
VOLTAGE	(V)		240
PHASES			3
FREQUENCY	(Hz)		50
NO OF POLES			4
FRAME			90L
SPEED			
	SYNCHRONOUS	(rpm)	1500
	FULL LOAD	(rpm)	1440
CURRENT			
	FULL LOAD	(Amps)	5.47
	LOCKED ROTOR	%	791
TORQUE			
	FULL LOAD TORQUE	(Nm)	9.94
	STARTING TORQUE	%	313.5
	MINIMUM TORQUE	%	236.5
	BREAKDOWN TORQUE	%	374
ROTOR INERTIA (J = GD²/4)		(Kgm ²)	0.006
EFFICIENCY			
	100% LOAD	%	87
	75% LOAD	%	86
	50% LOAD	%	84
POWER FACTOR			
	100% LOAD	%	76
	75% LOAD	%	67
	50% LOAD	%	53
INSULATION CLASS			H
ENCLOSURE TYPE			TEFC
IP RATING			66
WEIGHT OF MOTOR		kgs	29
BEARINGS			
	DRIVE END		6205 ZZ C3
	NON DRIVE END		6205 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M		dbA	47
DESIGN STANDARD			AS1359
CERTIFICATION			
TEMPERATURE RISE ABOVE AMBIENT			< 80 DEG C