



DATASHEET

MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

MOTOR SERIES	MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
START METHOD			DIRECT ON LINE
KW RATING			1.5
VOLTAGE	(V)		240
PHASES			3
FREQUENCY	(Hz)		50
NO OF POLES			6
FRAME			100L
SPEED			
	SYNCHRONOUS	(rpm)	1000
	FULL LOAD	(rpm)	950
CURRENT			
	FULL LOAD	(Amps)	5.88
	LOCKED ROTOR	%	735
TORQUE			
	FULL LOAD TORQUE	(Nm)	15.08
	STARTING TORQUE	%	258.5
	MINIMUM TORQUE	%	247.5
	BREAKDOWN TORQUE	%	308
ROTOR INERTIA (J = GD²/4)		(Kgm ²)	0.015
EFFICIENCY			
	100% LOAD	%	84
	75% LOAD	%	84
	50% LOAD	%	81.5
POWER FACTOR			
	100% LOAD	%	73
	75% LOAD	%	67
	50% LOAD	%	54
INSULATION CLASS			H
ENCLOSURE TYPE			TEFC
IP RATING			66
WEIGHT OF MOTOR		kgs	39
BEARINGS			
	DRIVE END		6206 ZZ C3
	NON DRIVE END		6305 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M		dbA	45
DESIGN STANDARD			AS1359
CERTIFICATION			
TEMPERATURE RISE ABOVE AMBIENT			< 80 DEG C