



DATASHEET

MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

MOTOR SERIES	MAX-E3 MINING Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
START METHOD			DIRECT ON LINE
KW RATING			2.2
VOLTAGE	(V)		240
PHASES			3
FREQUENCY	(Hz)		50
NO OF POLES			2
FRAME			90L
SPEED			
	SYNCHRONOUS	(rpm)	3000
	FULL LOAD	(rpm)	2900
CURRENT			
	FULL LOAD	(Amps)	7.56
	LOCKED ROTOR	%	892
TORQUE			
	FULL LOAD TORQUE	(Nm)	7.23
	STARTING TORQUE	%	374
	MINIMUM TORQUE	%	324.5
	BREAKDOWN TORQUE	%	445.5
ROTOR INERTIA (J = GD²/4)		(Kgm ²)	0.004
EFFICIENCY			
	100% LOAD	%	87.5
	75% LOAD	%	87
	50% LOAD	%	85
POWER FACTOR			
	100% LOAD	%	80
	75% LOAD	%	72
	50% LOAD	%	58
INSULATION CLASS			H
ENCLOSURE TYPE			TEFC
IP RATING			66
WEIGHT OF MOTOR		kgs	29
BEARINGS			
	DRIVE END		6205 ZZ C3
	NON DRIVE END		6205 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M		dbA	55
DESIGN STANDARD			AS1359
CERTIFICATION			
TEMPERATURE RISE ABOVE AMBIENT			< 80 DEG C