



DATASHEET

TECO FLAMEPROOF TEFC

MOTOR SERIES	TECO FLAMEPROOF TEFC	
START METHOD		DIRECT ON LINE
KW RATING		4
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		112M
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1455
CURRENT		
FULL LOAD	(Amps)	8.13
LOCKED ROTOR	%	800
TORQUE		
FULL LOAD TORQUE	(Nm)	26.9
STARTING TORQUE	%	230
MINIMUM TORQUE	%	200
BREAKDOWN TORQUE	%	345
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.0178
EFFICIENCY		
100% LOAD	%	88.3
75% LOAD	%	88
50% LOAD	%	77
POWER FACTOR		
100% LOAD	%	79.5
75% LOAD	%	72
50% LOAD	%	59
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	56
BEARINGS		
DRIVE END		6306 ZZ C3
NON DRIVE END		6306 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	50
DESIGN STANDARD		AS1359, BS4999, IEC60079-0:2004, IEC60079-1:2007, IEC60079-7:2006
CERTIFICATION		Ex de, Zone 1, IIC, T4 (T3 on VSD) 50°Camb
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C