



DATASHEET

TECO FLAMEPROOF TEFC

MOTOR SERIES	TECO FLAMEPROOF TEFC	
START METHOD		DIRECT ON LINE
KW RATING		5.5
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		132S
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1460
CURRENT		
FULL LOAD	(Amps)	10.4
LOCKED ROTOR	%	817
TORQUE		
FULL LOAD TORQUE	(Nm)	36.5
STARTING TORQUE	%	270
MINIMUM TORQUE	%	220
BREAKDOWN TORQUE	%	320
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.033
EFFICIENCY		
100% LOAD	%	90.5
75% LOAD	%	90.5
50% LOAD	%	89
POWER FACTOR		
100% LOAD	%	82.5
75% LOAD	%	76
50% LOAD	%	63.5
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	99
BEARINGS		
DRIVE END		6308 ZZ C3
NON DRIVE END		6306 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	55
DESIGN STANDARD		AS1359, BS4999, IEC60079-0:2004, IEC60079-1:2007, IEC60079-7:2006
CERTIFICATION		Ex de, Zone 1, IIC, T4 (T3 on VSD) 50°Camb
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C