



DATASHEET

3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM

MOTOR SERIES	3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM	
START METHOD		DIRECT ONLINE
KW RATING		930
VOLTAGE	(V)	3300
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		2
FRAME		450DA*-R
SPEED		
SYNCHRONOUS	(rpm)	3000
FULL LOAD	(rpm)	2984
CURRENT		
FULL LOAD	(Amps)	189.28
LOCKED ROTOR	%	640
TORQUE		
FULL LOAD TORQUE	(Nm)	2983
STARTING TORQUE	%	100
MINIMUM TORQUE	%	90
BREAKDOWN TORQUE	%	210
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	79.5
EFFICIENCY		
100% LOAD	%	96.2
75% LOAD	%	96.1
50% LOAD	%	95.6
POWER FACTOR		
100% LOAD	%	89.6
75% LOAD	%	88.3
50% LOAD	%	83.4
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	5430
BEARINGS		
DRIVE END		6220C3
NON DRIVE END		6220C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	84
DESIGN STANDARD		IEC60034
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C