



# DATASHEET

## MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

<b>MOTOR SERIES</b>	MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
<b>START METHOD</b>			DIRECT ONLINE
<b>KW RATING</b>			0.37
<b>VOLTAGE</b>	(V)		240
<b>PHASES</b>			3
<b>FREQUENCY</b>	(Hz)		50
<b>NO OF POLES</b>			4
<b>FRAME</b>			71
<b>SPEED</b>			
	SYNCHRONOUS	(rpm)	1500
	FULL LOAD	(rpm)	1405
<b>CURRENT</b>			
	FULL LOAD	(Amps)	1.73
	LOCKED ROTOR	%	530
<b>TORQUE</b>			
	FULL LOAD TORQUE	(Nm)	2.51
	STARTING TORQUE	%	357.5
	MINIMUM TORQUE	%	297
	BREAKDOWN TORQUE	%	335.5
<b>ROTOR INERTIA (J = GD<sup>2</sup>/4)</b>		(Kgm <sup>2</sup> )	0.0013
<b>EFFICIENCY</b>			
	100% LOAD	%	74.5
	75% LOAD	%	73
	50% LOAD	%	68.5
<b>POWER FACTOR</b>			
	100% LOAD	%	69.5
	75% LOAD	%	60.5
	50% LOAD	%	48
<b>INSULATION CLASS</b>			F
<b>ENCLOSURE TYPE</b>			TEFC
<b>IP RATING</b>			66
<b>WEIGHT OF MOTOR</b>		kgs	13
<b>BEARINGS</b>			
	DRIVE END		6202 ZZ C3
	NON DRIVE END		6202 ZZ C3
<b>NO LOAD SOUND PRESSURE LEVEL @ 1M</b>		dbA	50
<b>DESIGN STANDARD</b>			AS1359
<b>CERTIFICATION</b>			
<b>TEMPERATURE RISE ABOVE AMBIENT</b>			< 80 DEG C