



DATASHEET

MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

MOTOR SERIES	MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
START METHOD			DIRECT ON LINE
KW RATING			1.1
VOLTAGE	(V)		240
PHASES			3
FREQUENCY	(Hz)		50
NO OF POLES			2
FRAME			80
SPEED			
	SYNCHRONOUS	(rpm)	3000
	FULL LOAD	(rpm)	2815
CURRENT			
	FULL LOAD	(Amps)	3.68
	LOCKED ROTOR	%	845
TORQUE			
	FULL LOAD TORQUE	(Nm)	3.72
	STARTING TORQUE	%	330
	MINIMUM TORQUE	%	286
	BREAKDOWN TORQUE	%	363
ROTOR INERTIA (J = GD²/4)		(Kgm ²)	0.002
EFFICIENCY			
	100% LOAD	%	84.5
	75% LOAD	%	84
	50% LOAD	%	82
POWER FACTOR			
	100% LOAD	%	85
	75% LOAD	%	79
	50% LOAD	%	66
INSULATION CLASS			F
ENCLOSURE TYPE			TEFC
IP RATING			66
WEIGHT OF MOTOR		kgs	20
BEARINGS			
	DRIVE END		6204 ZZ C3
	NON DRIVE END		6204 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M		dbA	53
DESIGN STANDARD			AS1359
CERTIFICATION			
TEMPERATURE RISE ABOVE AMBIENT			< 80 DEG C