



DATASHEET

MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

MOTOR SERIES	MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
START METHOD			DIRECT ON LINE
KW RATING			3
VOLTAGE	(V)		240
PHASES			3
FREQUENCY	(Hz)		50
NO OF POLES			6
FRAME			132S
SPEED			
	SYNCHRONOUS	(rpm)	1000
	FULL LOAD	(rpm)	970
CURRENT			
	FULL LOAD	(Amps)	10.43
	LOCKED ROTOR	%	746
TORQUE			
	FULL LOAD TORQUE	(Nm)	29.54
	STARTING TORQUE	%	220
	MINIMUM TORQUE	%	198
	BREAKDOWN TORQUE	%	324.5
ROTOR INERTIA (J = GD²/4)		(Kgm ²)	0.039
EFFICIENCY			
	100% LOAD	%	88.8
	75% LOAD	%	87.5
	50% LOAD	%	86
POWER FACTOR			
	100% LOAD	%	78
	75% LOAD	%	71
	50% LOAD	%	59
INSULATION CLASS			F
ENCLOSURE TYPE			TEFC
IP RATING			66
WEIGHT OF MOTOR		kgs	75
BEARINGS			
	DRIVE END		6308 ZZ C3
	NON DRIVE END		6306 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M		dbA	51
DESIGN STANDARD			AS1359
CERTIFICATION			
TEMPERATURE RISE ABOVE AMBIENT			< 80 DEG C